



Kseibi SDS-Plus 4-Cutter Masonry Drill Bit

4-cutter control for SDS-plus drilling

Kseibi

Highlights

- SDS-plus shank for compatible rotary hammer drills
- 4-cutter tip design for controlled masonry drilling
- Spiral flute helps move dust out of the hole
- Spray-painted surface finish
- Suitable for concrete, brick and masonry work
- Available in diameters from 6 mm to 22 mm
- Selected 6.5 mm sizes also available
- Lengths available from 110 mm to 1000 mm
- Useful for anchors, fixings and installation work
- Wide size range helps match the job accurately

Key Features

- SDS-Plus Shank — Designed with an SDS-plus shank for secure fitment in compatible rotary hammer drills.
- 4-Cutter Tip — The 4-cutter head profile is built for steady drilling in concrete and masonry materials.
- Spiral Flute Body — The visible flute pattern helps carry dust and debris away from the cutting end during drilling.
- Extensive Size Choice — Available in multiple diameters and lengths, from shorter fixing sizes to long 1000 mm options.
- Job-Ready Finish — Finished with a spray-painted surface for a durable, practical tool suited to regular site use.

Variants & References

size	Internal Ref.
6 x 110mm	595006
8 x 110mm	595012
10 x 110mm	595015
6 x 160mm	595069
6.5 x 160mm	595070

8 x 160mm	595075
10 x 160mm	595081
12 x 160mm	595087
14 x 160mm	595093
6 x 210mm	595150
6.5 x 210mm	595151
8 x 210mm	595156
10 x 210mm	595162
12 x 210mm	595168
14 x 210mm	595174
16 x 210mm	595177
18 x 210mm	595183
6 x 260mm	595243
8 x 260mm	595249
10 x 260mm	595255
12 x 260mm	595261
14 x 260mm	595267
16 x 260mm	595270
6 x 310mm	595342
8 x 310mm	595348
10 x 310mm	595351
12 x 310mm	595354
14 x 310mm	595357
16 x 310mm	595360
18 x 310mm	595363
10 x 460mm	595435
12 x 460mm	595438
14 x 460mm	595441
16 x 460mm	595447
14 x 600mm	595562
10 x 1000mm	595597

12 x 1000mm	595600
14 x 1000mm	595603
16 x 1000mm	595606
18 x 1000mm	595609
20 x 1000mm	595612
22 x 1000mm	595615

Specifications

Shank Type	SDS-plus shank
Tip design	4-cutter
Flute style	Spiral
Surface finish	Spray-painted

Specifications by Variant

Specification	6 x 11 0mm	8 x 11 0mm	10 x 1 10m m	6 x 16 0mm	6.5 x 160m m	8 x 16 0mm	10 x 1 60m m	12 x 1 60m m	14 x 1 60m m	6 x 21 0mm
Head	—	—	—	Phillip s (cro ss) head	—	Phillip s (cro ss) head	Phillip s (cro ss) head	—	—	Phillip s (cro ss) head
Tip	—	—	—	—	—	—	—	Slotte d tip	—	—